

APC Smart-UPS 2200XLINET

APC Smart-UPS 2200XLINET - UPS - 2200 VA - external - UPS battery - 4 x lead acid - 17 Ah - 9 output connector(s)

Part Number: SU2200XLINET



Description

With Smart-UPS XL, now available in standard and rack-mount configurations, mission-critical applications can ride through a power outage, whether it lasts for a few seconds or several hours. Example applications requiring long runtimes include telephone PBX's, order entry database servers, computers supporting manufacturing or service operations, and critical data communications links. Extra runtime (up to 100 hours) can be added by simply plugging in battery packs.

The modular XL series can be delivered by popular shippers without special arrangements for the extra size and weight associated with other extended-run UPSs. Because the batteries are packaged in an enclosure separate from the electronics, they operate at reduced temperatures. Battery life is further enhanced through the use of a precision low-ripple float charger. For most extended-run UPSs, on-site repair requires an expensive service contract and a wait for factory authorized repair, In the case of the XL Series, any user can safely plug in new batteries or replace faulty UPS electronics or battery enclosure in minutes.

Main Specifications

Product Description	APC Smart-UPS 2200XLINET - UPS - 2200 VA - UPS battery - lead acid - 17 Ah
Device Type	UPS
Form Factor	External
Dimensions (WxDxH)	7.7 in x 21.5 in x 17 in
Weight	121.3 lbs
Load Rating	Small LAN / file server
Input Voltage	AC 230 V AC 230 V \pm 5%
Power Provided	2200 VA
Output connector(s)	9 x power IEC 320 EN 60320 C13, power IEC 320 EN 60320 C19
Battery	UPS battery - lead acid - 4 (installed) / 14 (max) - 12 V
Capacity	17 Ah
Average Run Time	8 min
System Requirements	Microsoft DOS, Microsoft Windows 3.x, Microsoft Windows 95, Microsoft Windows 98, Microsoft Windows NT 3.51, Microsoft Windows NT 4.0, Novell NetWare 3.2, Novell NetWare 3.11, Novell NetWare 4.0