

APC Smart-UPS 620INET - UPS - 620 VA - external - UPS battery lead acid - 4 output connector(s)

Part Number: SU620INET



Description

Protect both the computer and the data stored on it with APC's Smart-UPS 620. This line interactive UPS corrects power sags and surges, provides instant power via battery during failures, and protects both AC and phone lines to guard against electrical damage on both lines. It is suitable for small business, departmental and desktop server power protection.

The Smart-UPS 620 has a 620 volt-amp, 390 watt capacity. In addition to four AC outlets, it has data line protection for fax, modem or 100Base-TX network protection. Data lines provide another path to destruction for power surges and spikes, so protecting the incoming phone lines is an important part of the power protection puzzle. In addition to full-time surge suppression, this model provides EMI/RFI noise isolation to protect data files from contamination. The Smart-UPS 620 protects equipment against surges up to 320 Joules, and it evens out varying voltage levels with its exclusive Double SmartBoost and SmartTrim protection. The unit either boosts or trims voltage to provide regulated power to sensitive equipment. The Smart-UPS 620 features a user-replaceable, hot-swappable battery to provide instant power in brownout situations, and allow time for graceful shutdowns when the power completely fails. The CellGuard intelligent battery management circuitry monitors battery performance to maximize battery life. This model comes with PowerChute Plus software for advanced power management and diagnostics, with support for Win NT Server, Win95, Novell Netware and SCO UNIX operating systems.

Main Specifications

Product Description	APC Smart-UPS 620INET - UPS - 620 VA - UPS battery - lead acid
Device Type	UPS
Form Factor	External
Dimensions (WxDxH)	4.7 in x 14.5 in x 6.6 in
Weight	27.1 lbs
Localization	Australia, China, Asia, India, Latin America, Middle East, Africa, South Pacific, Western Europe, Eastern Europe
Load Rating	Small LAN / file server
Input Voltage	AC 230 V
Output Voltage	AC 230 V (50/60 Hz)
Power Provided	620 VA
Output connector(s)	4 x power IEC 320 EN 60320 C13
Battery	UPS battery - lead acid
Battery Form Factor	Internal
Average Run Time	5.5 min at full load