

APC Smart-UPS 750XL

APC Smart-UPS 750XL - UPS - 750 VA - external - UPS battery lead acid - 8 output connector(s)

Part Number: SUA750XLI



Description

Smart-UPS protects your data by supplying network-grade battery backup when power fails. With PowerChute plus software the uninterruptible power supply (UPS) will safely store data and shut down your network operating system before the battery is fully discharged, whether you're there or not. SmartSlot internal accessory slot allows you to install optional accessories to enhance the performance of your UPS. APC Smart-UPS is the perfect UPS for file servers, minicomputers, UNIX CPU's, Internet hubs, telecommunications systems and other mission-critical applications.

Smart-UPS XL models (Smart-UPS models with XL extensions in their names and part numbers) allow for expanding runtime by simply plugging in additional battery packs.

Main Specifications

Product Description	APC Smart-UPS 750XL - UPS - 750 VA - UPS battery - lead acid
Device Type	UPS
Form Factor	External
Dimensions (WxDxH)	6.7 in x 17.3 in x 8.5 in
Weight	53.1 lbs

Localization	Belgium, Bahrain, Jordan, Kuwait, Lebanon, Oman, Saudi Arabia, Yemen, United Arab Emirates, Afghanistan, Albania, Argentina, Armenia, Aruba, Australia, Benin, Bulgaria, Cameroon, China, Colombia, Cooks Island, Czech Republic, Estonia, Fiji, Indonesia, Israel, Lithuania, Papua New Guinea, Senegal, South Africa, Vietnam, Ukraine, Venezuela, Zaire, Belize, Chile, Hong Kong, Iceland, Iran, Mexico, Myanmar, New Zealand, Romania, Sri Lanka, Taiwan, Thailand, Virgin Islands, Malaysia, Singapore, Puerto Rico, Luxembourg, Hungary, Cyprus, Brunei, Iraq, India, Ghana, Kenya, Sierra Leone, Nigeria, Malawi, Zambia, Uganda, Tanzania, Bolivia, Uruguay, Peru, Paraguay, Ecuador, Honduras, Guatemala, Costa Rica, Salvador, Panama, Nicaragua, Dominican Republic, Jamaica, Botswana, Angola, Algeria, Chad, Burkina Faso, Ethiopia, Falkland Isles, Cote D'Ivoire, Congo, Gabon, Mali, Liechtenstein, Gibraltar, Gambia, Lesotho, Mauritania, Malta, Somalia, Rwanda, Niger, Mozambique, Morocco, Togo, Zimbabwe, Sudan, Bangladesh, Cambodia, Philippines, Nepal, Yugoslavia, Belarus, Bosnia, Croatia, Kazakhstan, Macedonia, Slovakia, Slovenia, Korea, Latvia, Azerbaijan, Guyana, Uzbekistan, Moldova, Herzegovina, Georgia, Bhutan, Barbados, Antigua and Barbuda, Cayman Islands, East Timor, Cuba, Anguilla, Andorra, Burundi, Central African Republic, Djibouti, Equatorial Guinea, Guinea, Liberia, Namibia, Turkmenistan, Western Sahara, Netherlands Antilles, Austria, Brazil, Denmark, Finland, France, Germany, Italy, Netherlands, Norway, Poland, Portugal, Russia, Spain, Sweden, Switzerland, United Kingdom, Greece, Turkey, Ireland
Input Voltage	AC 230 V
Output Voltage	AC 230 V
Power Provided	750 VA
Output connector(s)	8 x power IEC 320 EN 60320 C13
Battery	UPS battery - lead acid
Battery Form Factor	Plug-in module
Average Run Time	18.3 min at full load